

REFERENCE GUIDES

sdr-35 pvc sewer pipe data

NOM. SIZE	PIPE O.D.	WALL THICKNESS	WEIGHT PER FOOT (lbs)
			PIPE*
4	4.215	.120	1.053
6	6.275	.180	2.361
8	8.400	.240	4.222
10	10.500	.300	6.617
12	12.500	.360	9.480
15	15.300	.437	14.219
18	18.701	.536	21.510
21	22.047	.632	30.261
24	24.803	.711	38.642

* BASED ON 13' LENGTH

glass pipe data

PIPE SIZE	PIPE O.D.	SCHEDULE	WALL THICKNESS	WEIGHT PER FOOT (lbs)	
				PIPE*	PIPE FILLED WITH WATER
1	1.31	HEAVY	.16	.60	.95
1-1/2	1.84	REGULAR	.12	.64	1.53
		HEAVY	.17	.87	1.63
2	2.34	REGULAR	.14	.94	2.39
		HEAVY	.17	1.10	2.46
3	3.41	REGULAR	.17	1.60	4.79
		HEAVY	.20	2.00	5.06
4	4.53	REGULAR	.20	2.60	8.39
		HEAVY	.26	3.40	8.84
6	6.66	REGULAR	.24	4.70	17.48
		HEAVY	.33	6.30	18.72

NOTE:

Spacing of hangers for glass pipe should be every 8' to 10". Hangers should be felt lined or vinyl coated.