



“E” dimension includes exposed rod threads beyond bottom of the hex nut. Exposed rod thread dimension is equal to the diameter of the rod used.



Materials/Finishes:	Plastic Coated Electro-Galvanized Steel (110PC)
Variants:	N/A
Service:	Designed for the suspension of non-insulated stationary pipe lines in light duty applications. Plastic coating prevents pipe from coming in contact with hanger; resulting in noise and vibration reduction as well as the prevention of electrolysis between pipe and hanger.
Approvals:	Complies with Federal Specification WW-H-171-E (Type# 12) and Manufacturers' Standardization Society MSS SP-58 and SP-69 (Type# 1).
Ordering:	Specify figure number and pipe size
Notes:	Top of hanger as well as nut and cross bolt are electro-galvanized and bottom of hanger is plastic coated.

PIPE SIZE	PIPE OD	BOLT	A	B	C	E	F	WGT EACH (LBS)	MAX REC LOAD (LBS)
3/8	0.625	1/4	3/8	1-7/8	2-3/16	1-1/8	1/2	0.12	150
1/2	0.840	1/4	3/8	1-3/4	2-1/8	1	1/2	0.12	150
3/4	1.050	1/4	3/8	1-13/16	2-5/16	1-1/16	1/2	0.12	250
1	1.315	1/4	3/8	2-1/8	2-3/4	1-5/16	3/4	0.12	250
1 1/4	1.660	1/4	3/8	2-1/2	3-1/4	1-3/4	1-5/16	0.18	250
1 1/2	1.900	1/4	3/8	2-13/16	3-13/16	2-1/16	1-1/8	0.24	250
2	2.375	1/4	3/8	3-5/16	4-1/2	2-9/16	1-1/4	0.26	250
2 1/2	2.875	1/4	1/2	4-1/2	5-15/16	3-7/16	2-1/16	0.58	350
3	3.500	5/16	1/2	4-13/16	6-9/16	3-3/4	1-7/8	0.66	350
3 1/2	4.000	5/16	1/2	5-15/16	7-7/8	4-7/8	2-5/8	0.82	350
4	4.500	3/8	1/2	6-1/16	8-5/16	5	2-3/8	0.94	400
5	5.563	1/2	5/8	5-11/16	8-7/16	4-5/16	1-7/16	2.04	1430
6	6.625	1/2	3/4	6-13/16	10-1/8	5-3/16	1-3/4	2.80	1940
7	7.625	1/2	3/4	7-13/16	11-5/8	6-3/16	2	3.24	2000
8	8.625	5/8	3/4	8-1/16	12-7/16	6-1/4	1-7/8	4.46	2000
10	10.750	3/4	7/8	10	15-7/16	8	2-1/4	8.06	3600
12	12.750	3/4	7/8	11-9/16	18	9-9/16	2-13/16	10.34	3800

PROJECT INFORMATION			APPROVAL STAMP	
Project:			Notes:	
Address:				
Contractor:				
Engineer:				
Date:				
Approved	Approved as Noted	Not Approved		