



Materials/Finishes:	Plain Carbon Steel: Import (909BI)	Hot-Dip Galvanized: Import (909HDGI)
Variants:	Plain Carbon Steel (909B)	Electro-Galvanized (909G)
	Hot-Dip Galvanized (909HDG)	T-316 Stainless Steel (909SX)
Service:	Designed for use on high temperature piping installations.	
Approvals:	Complies with Manufacturers' Standardization Society MSS SP 58 and SP 69 (Type# 14).	
Ordering:	Specify size number, rod size, finish and part number. If other than standard dimension sizes required, specify size number, rod size, pin size and grip.	
Notes:	Forged clevis are standardly supplied with pin and cotter pins. When figure number 909 I is supplied hot-dip galvanized the threading is not tapped oversize.	

SIZE A	CLEVIS SIZE NO.	B	C	D	G GRIP	P PIN DIA.	T	W	WGT EACH (lbs)	MAX REC LOAD (lbs)	
										650°F	750°F
3/8-16	2	3-9/16	5/8	1-7/16	1/2	1/2	5/16	1-1/16	1.0	730	540
1/2-13	2	3-9/16	5/8	1-7/16	1/2	5/8	5/16	1-1/16	1.0	1350	1010
5/8-11	2	3-9/16	5/8	1-7/16	5/8	3/4	5/16	1-1/16	1.1	2160	1610
3/4-10	2-1/2	4	1	2-1/2	3/4	7/8	5/16	1-1/4	2.3	3230	2420
7/8-9	2-1/2	4	1	2-1/2	7/8	1	5/16	1-1/4	2.5	4480	3360
1-8	3	5-1/16	1-1/4	3	1	1-1/8	1/2	1-1/2	5.1	5900	4420
1-1/8-7	3	5-1/16	1-1/4	3	1-1/8	1-1/4	1/2	1-1/2	5.2	6230	5560
1-1/4-7	3	5-1/16	1-1/4	3	1-1/4	1-3/8	1/2	1-1/2	5.6	9500	7140
1-1/2-6	3-1/2	6	1-1/2	3-1/2	1-1/2	1-5/8	1/2	1-3/4	8.1	13800	10370
1-3/4-5	4	6	1-3/4	4	1-3/4	1-7/8	1/2	2	9.0	14700	14000

PROJECT INFORMATION	APPROVAL STAMP
Project:	Notes:
Address:	
Contractor:	
Engineer:	
Date:	
Approved Approved as Noted Not Approved	