
FIG. 155 steel beam clamp



Materials/Finishes:	Electro-Galvanized (155G)					
	T-304 Stainless Steel (155SS)	T-316 Stainless Steel (155SX)				
Variants:	N/A					
Service:	Designed for attaching hanger rods to be centered under beam flanges. The clamp provides a vertical adjustment of approximatly 2 inches.					
Approvals:	MSS SP-58 Type 21, FS WW-H-171E Type 21					
Ordering:	Specify figure number, finish, clamp size, beam thickness and flange width					
Notes:	Not available for flanges greater than 8 inches wide. Box style available in sizes 5 and 6. B dimension may vary 1/4" due to flange thickness variations.					

CLAMP SIZE	MATERIAL SIZE	A	В	C D MAX FLANGE		WEIGHT EACH (lbs) - FLANGE WIDTH (in)						MAX REC LOAD (lbs)		
						THICKNESS	4	5	5-1/2	6	6-1/2	7	8	
2	1/4 x 1-1/2	1/2	4	1-3/4		2.0	2.1	2.2	2.2	2.3	2.3	2.4	850	
3	3/8 x 1-1/2	5/8	4-1/2	2	1/2		2.9	3.1	3.3	3.3	3.5	3.5	3.7	1100
4	3/8 x 2	3/4	4-1/2	1	1/2	1/2	3.9	4.1	4.3	4.3	4.5	4.5	4.7	1500
5	1/2 x 2	7/8	5				6.0	6.2	6.3	6.3	6.6	6.6	6.9	2600
6	1/2 x 2-1/2	1	5	3/4	5/8		8.0	8.7	9.1	8.0	8.4	8.4	8.8	4300



PROJECT INFORMATION	APPROVAL STAMP				
Project:	Notes:				
Address:					
Contractor:					
Engineer:					
Date:					
Approved Approved as Noted Not Approved					