

9001FF - 9008FF

Materials/


Finishes:

flat fittings: linear

Zinc Plated (9001UFFZ)

T-304 Stainless (9001UFFSS)
T-316 Stainless (9001UFFSX)


9001FF square strut washer



| Materials/ Finishes: | Zinc Plated (9001FFZ) |
|-------------------------|----------------------------|
| | T-304 Stainless (9001FFSS) |
| | T-316 Stainless (9001FFSX) |
| Thickness: | 1/4" |


| ROD SIZE | WGT EACH (lbs) |
|----------|----------------|
| 1/4 | 0.18 |
| 3/8 | 0.18 |
| 1/2 | 0.17 |
| 5/8 | 0.16 |
| 3/4 | 0.16 |
| 7/8 | 0.15 |

$\begin{array}{c} 9001UFF \\ \text{u-saddle strut washer} \end{array}$



Thickness: 1/4" ROD SIZE WGT EACH (lbs) 1/4 0.18 3/8 0.18 1/2 0.17 5/8 0.16 3/4 0.16 7/8 0.15

| 9 | 0 | 0^{2} | 2] | 뎅 | P | | | | | L |
|----|----|---------|----|----|-----|-----|-----|----|-------|----|
| sq | ua | re | st | ru | t v | was | her | w/ | guide | es |




| Materials/ Finishes: | Zinc Plated (9003FFZ) |
|-------------------------|----------------------------|
| | T-304 Stainless (9003FFSS) |
| | T-316 Stainless (9003FFSX) |
| Thickness: | 1/4" |

| ROD SIZE | WGT EACH (lbs) |
|----------|----------------|
| 1/4 | 0.18 |
| 3/8 | 0.18 |
| 1/2 | 0.17 |
| 5/8 | 0.16 |
| 3/4 | 0.16 |

| 9003FF 2-hole splice plate 1-5/8" x 3-1/2" |
|--|
| 317 |


| Materials/ Finishes: | Zinc Plated (9004FFZ) |
|-------------------------|----------------------------|
| | T-304 Stainless (9004FFSS) |
| | T-316 Stainless (9004FFSX) |
| Thickness: | 1/4" |
| Hole Dim: | 9/16" |
| Wgt. each (lbs) | .34 |

| 9(|)() 4 | H | H | |
|-----|--------------|------|-------|-----|
| 2-h | ole | spli | ce pl | ate |
| sid | e to | side | stru | ıt |
| 1-5 | 5/8" | x 3- | 1/4" | |




| Materials/ | Zinc Plated (9005FFZ) |
|-----------------|----------------------------|
| Finishes: | T-304 Stainless (9005FFSS) |
| | T-316 Stainless (9005FFSX) |
| Thickness: | 1/4" |
| Hole Dim: | 9/16" |
| Wgt. each (lbs) | .46 |

9005FF 2-hole splice plate 1-5/8" x 4-5/8"




| Materials/ Finishes: | Zinc Plated (9006FFZ) |
|-------------------------|----------------------------|
| | T-304 Stainless (9006FFSS) |
| | T-316 Stainless (9006FFSX) |
| Thickness: | 1/4" |
| Hole Dim: | 9/16" |
| Wgt. each (lbs) | .55 |

9006FF 3-hole splice plate 1-5/8" x 5-3/8"



| Materials/ Finishes: | Zinc Plated (9007FFZ) |
|-------------------------|----------------------------|
| | T-304 Stainless (9007FFSS) |
| | T-316 Stainless (9007FFSX) |
| Thickness: | 1/4" |
| Hole Dim: | 9/16" |
| Wgt. each (lbs) | .76 |



| Materials/ | Zinc Plated (9008FFZ) |
|-----------------|----------------------------|
| Finishes: | T-304 Stainless (9008FFSS) |
| | T-316 Stainless (9008FFSX) |
| Thickness: | 1/4" |
| Hole Dim: | 9/16" |
| Wgt. each (lbs) | .95 |

| PROJECT INFORMATION | APPROVAL STAMP |
|---|----------------|
| Project: | Notes: |
| Address: | |
| Contractor: | |
| Engineer: | |
| Date: | |
| Approved Approved as Noted Not Approved | |