



Materials/Finishes:	Plain Carbon Steel (320BI)	Hot-Dip Galvanized (320HDGI)
	T-304 Stainless Steel (320SSI)	T-316 Stainless Steel (320SX)
Variants:	Domestic	Oversized Tap
	Special Thread Direction	
Service:	To provide up to 6 inches of adjustment. Normally tapped for UNC-2A thread (standard).	
Approvals:	Complies with Manufacturers' Standardization Society MSS SP-58 and SP-69 (Type# 13).	
Ordering:	Specify figure number, finish and size	
Notes:	When figure 320 is supplied hot-dip galvanized, it is not tapped oversize.	

320BI AND 320HDGI					
SIZE A	B	C	WGT EACH (lbs)	MAX REC LOAD (lbs)	
				650°F	700°F
3/8-16	6	7-1/8	0.42	730	540
1/2-13	6	7-1/2	0.65	1350	1010
5/8-11	6	7-7/8	0.98	2160	1610
3/4-10	6	8-1/4	1.50	3230	2420
7/8-11	6	8-5/8	1.90	4480	3360
1-8	6	9	2.60	5900	4420
1-1/8-7	6	9	4.20	6230	5560
1-1/4-7	6	9-1/8	4.50	9500	7140
1-1/2-6	6	9-3/4	6.40	13800	10370

T-304 STAINLESS STEEL				
SIZE A	B	C	WGT EACH (lbs)	MAX REC LOAD (lbs)
3/8-16	6	7-1/8	.29	800
1/2-13	6	7-1/2	.60	1400
5/8-11	6	7-7/8	.90	2240
3/4-10	6	8-1/4	1.30	3200
7/8-11	6	8-5/8	2.00	7200
1-8	6	9	2.90	10000

PROJECT INFORMATION	APPROVAL STAMP
Project:	Notes:
Address:	
Contractor:	
Engineer:	
Date:	
Approved      Approved as Noted      Not Approved	