
FIG. 159

adjustable rod beam clamp



Materials/Finishes:	Plain Carbon Steel (159B)	Electro-Galvanized (159G)			
Variants:	N/A				
Service:	Designed to be used in the suspension of a hanger rod from an I-beam. Recommended for flange widths from 4 inches minimum to 8 inches maximum.				
Approvals:	Complies with Federal Specifications WW-H-171-E (Type# 54), A-A-1192 A (Type# 27), and MSS SP-58 and SP-69 (Type# 27).				
Ordering:	Specify figure number, finish and rod size.				
Notes:	N/A				

SIZE A	MATERIAL SIZE	FLANGE WIDTH		В	Е	F	L	WGT EACH	MAX REC
		MIN	MAX					(lbs)	LOAD (lbs)
* 3/8-16	3ga x 1-1/4	3-1/2	8	2	3/8	1	2-3/4	0.97	300
1/2-13	3ga x 1-1/2	3-1/2	8	2	1/2	15/16	2-3/4	1.37	700
5/8-11	3ga x 1-3/4	3-1/2	8	2	5/8	7/8	2-3/4	1.84	1000
3/4-10	3/8 x 2-1/2	3-1/2	8	2-1/2	3/4	1-1/4	3-3/8	6.78	1800
* NOT AVAILABLE IN PLAIN CARBON STEEL									

PROJECT INFORMATION	APPROVAL STAMP			
Project:	Notes:			
Address:				
Contractor:				
Engineer:				
Date:				
Approved Approved as Noted Not Approved				