



Materials/Finishes	Plain Carbon Steel (57B)	Electro-Galvanized (57G)
	T-304 Stainless (57SS)	T-316 Stainless (57SX)
Variants:	Double Right Hand Threads (57RR)	Double Left Hand Threads(57LL)
	Left and Right Hand Threads (57LR)	
Service:	Designed for use in pipe hanger assemblies.	
Approvals:	N/A	
Ordering:	Specify figure number, finish, thread direction, rod size, length and thread length.	
Notes:	Threads are not chased on hot-dip galvanized rod.	

SIZE A	THREAD LENGTH B & C	LENGTH D	WGT/FT (lbs)	MAX REC LOAD (lbs)	
				650°F	750°F
1/4-20	SPECIFY	SPECIFY	0.12	240	210
3/8-16	SPECIFY	SPECIFY	0.29	730	540
1/2-13	SPECIFY	SPECIFY	0.54	1350	1010
5/8-11	SPECIFY	SPECIFY	0.83	2160	1610
3/4-10	SPECIFY	SPECIFY	1.25	3230	2420
7/8-9	SPECIFY	SPECIFY	1.70	4480	3360
1-8	SPECIFY	SPECIFY	2.23	5900	4420
1-1/8 - 7	SPECIFY	SPECIFY	2.81	6230	560
1-1/4 - 7	SPECIFY	SPECIFY	3.54	9500	7140
1-1/2 - 6	SPECIFY	SPECIFY	5.12	1380	10370

PROJECT INFORMATION			APPROVAL STAMP	
Project:			Notes:	
Address:				
Contractor:				
Engineer:				
Date:				
Approved	Approved as Noted	Not Approved		