



<b>Materials/Finishes:</b>	Plain Carbon Steel (275NCRB)	Electro-Galvanized (275NCRG)
	Hot-Dip Galvanized (275NCRHDG)	T-304 Stainless Steel (275NCRSS)*
	T-316 Stainless Steel (275NCRSX)*	
<b>Service:</b>	Designed for the support of pipe where longitudinal movement may occur due to expansion and contraction, and vertical adjustment is not necessary. May be bolted or welded to supporting member.	
<b>Approvals:</b>	Complies with Federal Specification A-A-1192 A (Type# 44) and Manufacturers' Standardization Society MSS SP-58 (Type# 44).	
<b>Ordering:</b>	Specify figure number, finish and roller size. Please remember to consider insulation thickness when sizing rollers	
<b>Notes:</b>	Hardware is Electro Galvanized. Mounting hardware not included. *Not available in 5, 7, or 24.	

HANGER SIZE	AXLE SIZE	B	C	D	E	F	WGT EACH (lbs)	MAX REC LOAD (lbs)
2	3/8	1-9/16	1-3/8	1-1/4	4-1/4	3/8	0.94	390
3	1/2	2-1/8	1-3/4	2	5-11/32	3/8	1.32	390
4	1/2	3-1/16	2-5/16	2	7-11/32	1/2	2.94	950
5	5/8	3-1/2	2-1/2	3	8-1/4	1/2	3.64	950
6	3/4	4-1/8	2-3/4	3-1/8	9-1/2	1/2	5.72	950
8	7/8	5-5/16	3	3-3/8	12-1/4	5/8	8.16	1350
10	7/8	6-9/16	3-5/8	5	14-1/2	5/8	11.96	1730
12	7/8	7-9/16	4-1/8	6	16-1/4	5/8	15.86	2400
14	1-1/8	8-3/16	4-11/16	6-1/2	18	3/4	21.58	3130
16	1-1/4	9-1/4	5-3/8	8-1/4	21	3/4	34.50	3970
18	1-1/4	10-7/16	6	9-1/4	22-7/8	3/4	36.50	4200
20	1-1/4	11-7/8	6-1/2	10-1/4	25-1/4	3/4	45.00	4550
24	1-1/2	14-1/4	7-7/8	12-1/4	30	7/8	77.50	6160

PROJECT INFORMATION	APPROVAL STAMP
Project:	APPROVED AS NOTED
Address:	NOTES:
Contractor:	
Engineer:	
Date:	
APPROVED	
NOT APPROVED	