



"E" Dimension includes exposed rod threads beyond bottom of hex nut. Exposed rod thread dimension is equal to the diameter of the rod used.



Materials/Finishes:	T-304 Stainless Steel (272SRSS)	T-316 Stainless Steel (272SRSX)
Service:	Designed for the suspension of pipe where longitudinal movement of pipe may occur due to expansion and contraction, and where vertical adjustment may be necessary.	
Approvals:	Complies with Federal Specification WW-H-171-E (Type# 44), A-A-1192 A (Type# 43) and Manufacturers' Standardization Society MSS SP-58 and SP-69 (Type# 43).	
Ordering:	Specify figure number, finish and roller size. Please remember to consider insulation thickness when sizing rollers	
Notes:	Stainless Steel hangers are recommended for applications where protection from a corrosive environment is required.	

SIZE NO.	A	B	C	D	F	L	CROSS ROD DIA.	MAX REC LOAD (lbs)
4	5/8	5-3/16	2-13/16	4-7/8	6-1/2	9-1/4	3/4	300
6	3/4	6-7/16	3-15/16	7	9-1/2	11-5/8	3/4	800
8	7/8	7-1/2	5-1/4	9	11-7/8	14	7/8	925
10	7/8	8-3/4	6-3/8	11	14-1/4	16-1/2	7/8	925
12	7/8	10-1/16	7-7/16	13	16-1/4	18-7/8	1-1/8	680
14	1	10-15/16	8-3/16	14-1/4	18	20-5/8	1-1/8	1200
16	1	12-13/16	9-5/16	16-7/8	21	24-3/8	1-1/4	1100
18	1	13-3/4	10-3/8	18-1/4	22-7/8	26-1/8	1-1/4	1200
20	1-1/4	15-1/16	11-5/16	20-1/4	25-1/2	28-11/16	1-1/4	1000

PROJECT INFORMATION	APPROVAL STAMP
Project:	APPROVED AS NOTED
Address:	NOTES:
Contractor:	
Engineer:	
Date:	
APPROVED	
NOT APPROVED	