



Materials/Finishes	Plain Carbon Steel (68B)	Electro-Galvanized (68G)
	Hot-Dip Galvanized (68HDG)	T-304 Stainless (68SS)
	T-316 Stainless (68SX)	
Service:	Designed for the attachment of hanger rod to concrete ceilings where vertical adjustment of hanger is desired.	
Ordering:	Specify figure number, finish and rod size.	
Notes:	Hot-Dip Galvanized attachment uses Electro-Galvanized Hardware.	

ROD SIZE	A	B	C	D	E	F	G	W	WGT EACH (lbs)	MAX REC LOAD (lbs)
3/8	1	8	10	5	2-1/4	9/16	3/8	2	11.60	730
1/2	1	8	10	5	2-1/8	9/16	3/8	2	11.60	1350
5/8	1	8	10	5	2-1/4	9/16	1/2	2	15.20	2160
3/4	1	8	10	5	2-1/4	11/16	1/2	2-1/2	16.10	3230
7/8	1	8	10	5	3-1/8	11/16	1/2	2-1/2	16.70	4480
1	2	8	12	6	3-1/2	13/16	3/4	3	35.00	5900
1-1/8	2	8	12	6	3-5/8	13/16	3/4	3	35.20	6230
1-1/4	2	8	12	6	3-5/8	13/16	3/4	4	40.90	9500

PROJECT INFORMATION	APPROVAL STAMP
Project:	APPROVED AS NOTED
Address:	NOTES:
Contractor:	
Engineer:	
Date:	
APPROVED	
NOT APPROVED	