




Materials/Finishes:	Plain Carbon Steel (216B)	Electro-Galvanized (216G)
	Hot-Dip Galvanized (216HDG)	T-304 Stainless Steel (216SS)
	T-316 Stainless Steel (216SX)	
Service:	Designed for the suspension of cold or hot pipe lines with heavy loads where no insulation is required.	
Approvals:	Complies with Federal Specifications WW-H-171-E (Type# 4), A-A-1192 A (Type# 4), and MSS SP-58 and SP-69 (Type# 4).	
Ordering:	Specify figure number, finish and pipe size	

PIPE SIZE	PIPE OD	BOLT	B	F	J	WGT EACH (lbs)	MAX REC LOAD (lbs)
3	3.500	3/4	3-1/8	1	4	2.67	3370
3-1/2	4.000	3/4	3-5/16	1	4-3/16	3.36	3515
4	4.500	7/8	3-3/4	1	4-7/8	5.93	3515
5	5.563	7/8	4-3/8	1	5-1/2	6.56	3515
6	6.625	1	5-1/4	1-1/8	6-5/8	12.40	4865
8	8.625	1	6-1/4	1-1/8	7-5/8	14.66	4865
10	10.750	1-1/4	7-11/16	1-1/4	9-1/16	23.45	6010
12	12.750	1-1/2	9-1/4	1-5/8	11-1/8	40.98	8675
14	14.000	1-1/2	10	1-5/8	11-7/8	56.00	9120
16	16.000	1-1/2	11-5/16	1-5/8	13-3/16	62.00	9120
18	18.000	2	14-1/2	3	18-1/2	129.00	13800
20	20.000	2	16	3	20	148.00	15300
24	24.000	2	18-1/2	3-1/4	23	200.00	16300
30	30.000	2-1/4	22-1/2	3-1/2	26	390.00	20500

PROJECT INFORMATION	APPROVAL STAMP
Project:	APPROVED AS NOTED
Address:	NOTES:
Contractor:	
Engineer:	
Date:	
APPROVED	
NOT APPROVED	