



"E" Dimension includes exposed rod threads beyond bottom of hex nut. Exposed rod thread dimension is equal to the diameter of the rod used.



11DIP:



AIS-11DIP:



Materials/Finishes:	Plain Carbon Steel (11DIPB)	Hot-Dip Galvanized (11DIPHDG)
	T-304 Stainless (11DIPSS)	T-316 Stainless (11DIPSX)
Variants	AIS Compliant (AIS11DIP)*	
Service:	Designed for the suspension of stationary AWWA ductile iron pipe and PVC C-900 pipe.	
Approvals:	Complies with Manufacturers' Standardization Society MSS SP-58 (Type# 1).	
Ordering:	Specify figure number, material, finish and pipe size.	
Notes:	For 3" DIP, use standard 11G0350. For sizes 8" and larger a spacer sleeve is added over the cross bolt. Upper locknut must be tightened securely to assure proper hanger performance. Stainless steel hangers are recommended for applications where protection from a corrosive environment is required. *Available in Plain and Hot-Dip Galvanized only	

PIPE SIZE AWWA	PIPE OD	BOLT	A	B	C	E	F	WGT EACH (LBS)	MAX REC LOAD (LBS)
4	4.800	3/8	5/8	6	8-1/2	4-5/8	2-1/8	1.32	1430
6	6.900	1/2	3/4	6-13/16	10-1/8	5-3/16	1-3/4	2.86	1940
8	9.050	5/8	3/4	8-5/16	13	6-7/8	1-7/8	4.56	2000
10	11.100	3/4	7/8	10-1/2	16-1/4	8-1/2	2-1/4	8.70	3600
12	13.200	3/4	7/8	11-3/4	18-3/4	9-3/4	2-13/16	11.08	3800
14	15.300	1	1	13	20-3/4	11-3/4	2-1/2	17.57	4200
16	17.400	1	1	15-1/4	25	13-1/2	3-3/8	25.38	4600
18	19.500	1-1/4	1	17-1/2	27-1/2	15-1/8	3-3/4	47.00	4800
20	21.600	1-1/4	1-1/4	18-1/2	29-1/2	16-3/8	3-3/4	50.50	4800
24	25.800	1-1/4	1-1/4	20-3/4	34	18-5/8	4	58.00	4800
30	32.000	1-1/4	1-1/4	26-5/8	43	24	5-3/16	75.00	6000

PROJECT INFORMATION	APPROVAL STAMP
Project:	APPROVED AS NOTED
Address:	NOTES:
Contractor:	
Engineer:	
Date:	
APPROVED	
NOT APPROVED	