



"E" Dimension includes exposed rod threads beyond bottom of hex nut. Exposed rod thread dimension is equal to the diameter of the rod used.



**Domestically  
Manufactured**  
Excluding 31CTI



<b>Materials/Finishes:</b>	Copper Epoxy Coated <i>Copper Gard</i> : Domestic (31CT)
<b>Variants:</b>	Copper Epoxy Coated <i>Copper Gard</i> : Imported (31CTI)
<b>Service:</b>	Designed for the suspension of non-insulated stationary pipe.
<b>Approvals:</b>	Complies with Manufacturers' Standardization Society MSS SP-58 and (Type# 7).
<b>Ordering:</b>	Specify figure number, finish and tube size
<b>Notes:</b>	Upper locknut must be tightened securely to assure proper hanger performance. COPPER-GARD products offer superior corrosion protection due to the epoxy coating over phosphate zinc coated steel. The alternative, copper plating that has been done historically is for identification purposes only and is not intended for corrosion protection. Refer to MSS-SP58 13.3.

PIPE SIZE	PIPE OD	A	B	C	E	F	WGT EACH (lbs)	MAX REC LOAD (lbs)
1/2	0.625	3/8	2-3/8	2-11/16	1-9/16	1-5/8	.10	610
3/4	0.875	3/8	2-1/4	2-11/16	1-5/16	1-1/4	.10	610
1	1.125	3/8	2-1/8	2-11/16	1-5/16	3/4	.10	610
1-1/4	1.375	3/8	2-3/16	2-7/8	1-9/16	1-1/4	.12	610
1-1/2	1.625	3/8	2-3/8	3-3/16	2	1-9/16	.12	610
2	2.125	3/8	2-3/4	3-13/16	2-3/8	1-11/16	.14	610
2-1/2	2.625	1/2	3-1/8	4-7/16	2	1-1/4	.30	610
3	3.125	1/2	3-3/16	4-3/4	1-7/8	13/16	.32	970
3-1/2	3.625	1/2	3-13/16	5-9/16	2-11/16	1-3/8	.38	970
4	4.125	1/2	3-7/8	5-5/16	2-3/4	1-3/16	.44	1130
* 5	5.125	1/2	5	7-9/16	3-13/16	1-3/4	.68	1130
* 6	6.125	1/2	5-5/8	8-11/16	4-7/16	1-7/8	.84	1130
<b>* NOT AVAILABLE AS IMPORTED</b>								

PROJECT INFORMATION	APPROVAL STAMP
Project:	APPROVED AS NOTED
Address:	NOTES:
Contractor:	
Engineer:	
Date:	
APPROVED	
NOT APPROVED	