




Materials/Finishes:	Electro-Galvanized with EPDM Insulation Liner (40HS)
Service:	Designed for the suspension of insulated and non-insulated pipe lines.
Approvals:	Complies with Federal Specification WWH-171-E (Type# 25), A-A-1192A (Type# 12), Manufacturers' Standardization Society SP-58 (Type# 12).
Ordering:	Specify figure number and CT or IPS Size.
Notes:	The "Handy Split" hinge device allows single handed installation. UV resistant EPDM rubber provides noise reduction. Temperature range is from -50° F through 230° F.

HANGER SIZE	PIPE SIZE (IPS)	PIPE SIZE (CTS)	METRIC SIZE (MM)	SCREW	A	B	C	D	WGT EACH (lbs)	MAX REC LOAD (lbs)
1	1/4	3/8	10-14	M6	3/8-16	7/8	2-3/16	1-3/8	.11	180
2	3/8	1/2	15-18	M6	3/8-16	15/16	2-3/8	1-1/2	.12	180
3	-	5/8	19	M6	3/8-16	1	2-3/8	1-5/8	.12	180
4	1/2	3/4	20-23	M6	3/8-16	1-1/16	2-9/16	1-3/4	.14	180
5	3/4	1	25-29	M6	3/8-16	1-3/16	2-3/4	2	.15	180
6	1	1-1/4	31-35	M6	3/8-16	1-1/4	3-1/8	2-1/4	.17	180
7	1-1/4	1-1/2	40-43	M6	3/8-16	1-7/16	3-1/2	2-1/2	.19	180
8	1-1/2	-	46-51	M6	3/8-16	1-9/16	3-3/4	2-3/4	.20	180
9	-	2	53-59	M6	3/8-16	1-11/16	3-15/16	3	.26	180
10	2	-	59-64	M6	3/8-16	1-3/4	4-1/8	3-1/4	.27	180
11	-	2-1/2	65-70	M6	3/8-16	1-15/16	4-7/16	3-1/2	.29	300
12	2-1/2	-	72-78	M6	3/8-16	2-1/16	4-3/4	3-3/4	.36	300
13	-	3	79-82	M6	3/8-16	2-1/4	5	4-1/16	.38	300
14	3	-	86-92	M6	3/8-16	2-7/16	5-7/16	4-7/16	.41	300
15	-	3-1/2	90-95	M6	3/8-16	2-1/2	5-9/16	4-9/16	.41	300
16	3-1/2	4	100-105	M6	3/8-16	2-3/4	6-1/8	5-1/16	.67	300
17	4	-	108-116	M6	3/8-16	2-15/16	6-7/16	5-7/16	.70	300

PROJECT INFORMATION	APPROVAL STAMP
Project:	APPROVED AS NOTED
Address:	NOTES:
Contractor:	
Engineer:	
Date:	
APPROVED	
NOT APPROVED	