


FIG. 41SS / 41SXI

T-304 and T-316 Stainless Steel Split Ring Hanger

v | 06.2024

LOCAL: 860 647 1431 • TOLL FREE: 800 243 4844 • ORDERS@EMPIREINDUSTRIES.COM • QUOTES@EMPIREINDUSTRIES.COM



Materials/Finishes:	T-304 Stainless (41SS)	T-316 Stainless (41SXI)
Service:	Designed for the suspension of non-insulated stationary pipe lines, horizontally or vertically.	
Approvals:	Complies with Manufacturers' Standardization Society MSS SP-58 (Type# 12).	
Ordering:	Specify figure number, material and pipe size.	
Notes:	Stainless steel hangers are recommended for applications where protection from a corrosive environment is required.	

PIPE SIZE	PIPE OD	SCREW	A	B	C	D	WGT EACH (LBS)	MAX REC LOAD (LBS)
3/8	0.675	10-24	3/8-16	11/16	1-13/16	1-3/16	0.084	180
1/2	0.840	10-24	3/8-16	3/4	2-1/8	1-3/16	0.098	180
3/4	1.050	10-24	3/8-16	7/8	2-1/2	1-9/16	0.112	180
1	1.315	10-24	3/8-16	1-1/8	2-3/4	2	0.147	180
1-1/4	1.660	10-24	3/8-16	1-5/16	3-3/16	2-3/8	0.181	180
1-1/2	1.900	10-24	3/8-16	1-7/16	3-3/8	2-5/8	0.214	180
2	2.375	10-24	3/8-16	1-5/8	3-15/16	3-1/16	0.300	180
2-1/2	2.875	1/4	1/2-13	2-1/8	5-3/16	3-13/16	0.580	300
3	3.500	1/4	1/2-13	2-1/2	5-11/16	4-5/8	0.720	300
4	4.500	1/4	1/2-13	2-7/8	6-3/4	5-9/16	1.020	300

PROJECT INFORMATION	APPROVAL STAMP
Project:	APPROVED AS NOTED
Address:	NOTES:
Contractor:	
Engineer:	
Date:	
APPROVED	
NOT APPROVED	