



**FIG. 95SS/SX**



<b>Materials/Finishes:</b>	T-304 Stainless Steel (95SS)	T-316 Stainless Steel (95SX)
<b>Variants:</b>	T-304 Stainless for DIP Sizes (95DIPSS)	
	T-316 Stainless for DIP Sizes (95DIPSX)	
<b>Service:</b>	For use in supporting horizontal piping away from the wall or floor. This clamp is also designed for non-load-bearing bracing on vertical piping runs (not to be used as a riser type support). This clamp can be furnished with "B" dimensions to suit field conditions.	
<b>Ordering:</b>	Specify figure number, pipe type, finish and pipe size	
<b>Notes:</b>	<b>Available in IP (95) and Ductile Iron Pipe (95DIP) Sizes.</b> Custom B dimension available.	

PIPE SIZE	PIPE OD	BOLT	B	C	D	WGT EACH (lbs)	MAX REC LOAD (lbs)
1/2	0.840	3/8	2-1/2	6	7/16	1.25	200
3/4	1.050	3/8	2-1/2	7-3/8	7/16	1.25	200
1	1.350	3/8	2-5/8	7-7/8	7/16	1.33	200
1-1/4	1.660	3/8	2-13/16	8	7/16	1.42	200
1-1/2	1.900	3/8	2-15/16	8-1/4	7/16	1.49	200
2	2.375	3/8	3-3/16	9-3/8	7/16	2.03	410
2-1/2	2.875	3/8	3-7/16	10-1/4	7/16	2.25	410
3	3.500	3/8	3-3/4	11	7/16	2.50	410
3-1/2	4.000	3/8	4	11-1/4	7/16	2.75	410
4	4.500	1/2	4-1/4	11-1/2	9/16	3.68	600
6	6.625	1/2	5-5/16	14-1/2	9/16	6.80	850
8	8.625	1/2	6-5/16	17-1/4	9/16	8.20	850
10	10.750	3/4	7-3/4	23	13/16	21.42	870

PROJECT INFORMATION	APPROVAL STAMP
Project:	APPROVED AS NOTED
Address:	NOTES:
Contractor:	
Engineer:	
Date:	
APPROVED	
NOT APPROVED	